


MODELS (●)
HY900Si
HY3000i new
HY4000i
HY1000Si
HY2000Si

| CHARACTERISTICS | Frequency (Hz) | 50 Hz | 50 Hz | 50 Hz | 50 Hz | 50 Hz |
|-------------------|-----------------------------|------------------------|---------------|---------------|-------------------|-------------------|
| | Rated Power | 750 W / 0,75 kW | 3,0 kW | 3,5 Kw | 0,9 kW | 1,6 kW |
| | Maximum Power | 900 W / 0,90 kW | 3,3 kW | 3,8 Kw | 1,0 kW | 2,0 kW |
| | Voltage (V) | 230 | 230 | 230 | 230 | 230 |
| | Current (A) | 4 | 13 | 15,2 | 4,4 | 9,0 |
| | Plugs | 1x16A | 2x16A | 2x16A | 1x16A | 2x16A |
| | Digital Display | - | Si | Si | Si | Si |
| | Fuel tank capacity (L) | 2,4 | 12 L | 10 L | 2,1 | 3,8 |
| | Function at 50% load (hr.) | 4,5 | 5,5 h | 7 h | 4 | 4,5 |
| | Noise level at 7m; 50% (dB) | 58 | 73 | 73 | 58 | 58 |
| DC Output 12(V/A) | 12V 4A / USB | 12 / 5 | 12 / 5 | 12 / 5 | 12/5 | |
| Battery (Ah) | - | - | - | - | - | |
| ENGINE | Engine Type | 4T Petrol | Petrol | Petrol | 4T Petrol- | 4T Petrol- |
| | HYUNDAI Engine Model | IC40i | IC210 | IC210 | HX144F | HX149F |
| | Power (HP) | 1,4 | 7 | 7 | 1,8 | 3,2 |
| | Starting Mode | Manual | Manual | Manual | Manual | Manual |
| | Displacement (cc) | 40 | 208 | 208 | 50 | 79 |
| | Oil Capacity (L) | 0,30 | 0,5 | 0,5 | 0,25 | 0,41 |
| ALTER. | Alternator | A9i | A26i | A4i | A10i | A20i |
| | Rated Power (kVA) | 0,9 | 3 | 3,5 | 0,9 | 2 |
| | Power Factor (cos φ) | 1 | 1 | 1 | 1 | 1 |
| | Voltage Regulation Type | Electrónica | Electronic | Electronic | Electronic | Electronic |
| PACKAGING | Net Weight (kg) | 9 | 32 | 43 | 14 | 20 |
| | Gross Weight (kg) | 11 | 36 | 45 | 16 | 22 |
| | Product Dimensions (mm) | 210x392x350 | 445x425x445 | 400x450x450 | 451x242x379 | 575x330x507 |
| | Packaging Dimensions (mm) | 245x430x390 | 500x480x510 | 420x470x470 | 490x300x410 | 610x350x530 |