

SKANBATT

DUAL PURPOSE SERIES - PREMIUM TECHNICAL DATASHEET

SKANBATT Dual Purpose 12V 230Ah 1400CA

Dual Purpose battery for starting and onboard service applications
Fitment: Large case · Base hold-down: - · Polarity layout: + left · Terminal type: Standard battery terminals

Technical Specifications

Parameter	Value
Nominal Voltage	12 V
Capacity (20h)	230 Ah
Cold Cranking (CCA/EN)	1150 A
Starting Rating (CA)	1400 A
Reserve Capacity (RC)	420 min
Dimensions (L x W x H)	513 x 276 x 210 mm
Weight	58 kg
Technology	Flooded lead-acid dual purpose battery

About SKANBATT Dual Purpose

SKANBATT Dual Purpose batteries are designed for leisure applications where both reliable engine starting and stable onboard power are required. They provide a practical balance between starting performance and reserve capacity, making them suitable for boats, motorhomes, caravans and other recreational installations. Compared with pure starter batteries, Dual Purpose models offer improved support for service loads such as lighting, pumps, control systems and electronics. This makes them ideal where one battery must cover both tasks in a simple and robust installation. SKANBATT Dual Purpose 12V 230Ah 1400CA is a 12 V Dual Purpose battery developed for large boats, motorhomes and high-demand off-grid leisure installations. It delivers reliable engine starting together with stable energy supply for everyday leisure use.

Charging, Maintenance & Storage

- Recommended charging voltage: 14.4 V at 25 C (unless equipment or battery manufacturer specifies otherwise).
- Float / maintenance voltage: 13.5 - 13.8 V at 25 C.
- Temperature compensation is recommended for optimal charging.
- Recharge promptly after deep discharge for best service life.
- Avoid prolonged undercharge and prolonged overcharge.
- For storage: keep the battery fully charged and recharge every 3 - 6 months depending on temperature.

SKANBATT - Battery Solutions Made Easy

Specifications are typical values and may vary depending on production tolerances and operating conditions.