

DELTA 3 Max Plus (2048Wh)

Colour: Silver
Capacity: 2048Wh
Net Weight: Approx. 22.1 kg
Dimensions: 494 × 242 × 305 mm
Total Output Ports: 10
Total Output Power: 3581W Max
UPS: 10 ms + HID
Warranty Period: 3+2 years
Volume: 600W ≤ 25 dB



AC Output

Number of AC Outlets	Output Priority	Max AC Output
4	Yes	3000W
Surge Output	X-Fusion	Max X-Boost Output
6000W	Yes	3900W
Output Voltage		
230V~50Hz, 3000W Total 13A Max per port (×4)		

DC Output

Number of DC Outlets	USB-A	USB-C
6	1 × 18W Max	1 × 140W Max (HID) 2 × 45W Max (Total 45W)
12V DC Output		
378W Max Car Power Output × 1:12.6V==10A Anderson Output × 1:12.6V==30A		

Input

Utility Power Charging	Input Voltage	0-80% Charge Time
2300W (Depending on Input Voltage)	220-240V~10A 50/60Hz	47 min
Solar Charging	Alternator Charging	0-100% Charge Time
1000W (2 × 500W)	1000W Max Through 4+8 Port	68 min
Generator Charging	Car Charging	
2400W Max	12V/24V==8A	

Battery

Battery Chemistry	Type of Extra Battery Ports	CTC Technology
LFP	4+8	CTC
Extra Battery Compatibility	Number of Extra Battery Ports	Max Capacity with Extra Battery
D2M/D3MP D3/DP3 EB	1(expandable to 2)	Up to 10kWh with 2 × DELTA Pro 3 Extra Battery

Connections

Screen	Wi-Fi	Bluetooth	App
Yes	Yes	Yes	Yes

Operating Conditions

Operating Altitude: ≤3000 m	Discharge Temperature: -10-45°C
Charge Temperature: 0-45°C	Storage Temperature: -10-45°C